

Customer No.: 31561
Application No.: 10/707,084
Docket No.: 10722-US-PA

AMENDMENT

To the Claims:

Claim 1. (currently amended) An UV photodetector, comprising:

a substrate;

a GaN-based semiconductor layer, disposed on the substrate, wherein the GaN-based semiconductor layer comprises a first protrusion portion, wherein the GaN-based semiconductor layer comprising:

a nucleation layer, disposed on the substrate;

an ohmic contact layer, disposed on the nucleation layer, wherein the ohmic contact layer comprises a second protrusion portion;

an active layer, disposed on the second protrusion portion, wherein the first protrusion portion is constructed by the second protrusion portion of the ohmic contact layer and the active layer;

a high-resistivity GaN-based interlayer, disposed on the first protrusion portion of the GaN-based semiconductor layer, and a material of the GaN-based interlayer comprising $\text{Al}_x\text{In}_y\text{Ga}_{1-x-y}\text{N}$, wherein $x \geq 0$, $y \geq 0$, $1 \geq x + y$;

a first electrode, disposed on the GaN-based interlayer; and

a second electrode disposed on a portion of the GaN-based semiconductor layer except for the first protrusion portion.

Claim 2. (original) The UV photodetector of claim 1, further comprising a first bonding pad, wherein the first bonding pad is disposed on the first electrode.

Customer No.: 31561
Application No.: 10/707,084
Docket No.: 10722-US-PA

Claim 3. (original) The UV photodetector of claim 1, further comprising a second bonding pad, wherein the second bonding pad is disposed on the second electrode.

Claim 4. (original) The UV photodetector of claim 1, wherein the substrate is comprised of an aluminum oxide (sapphire) substrate, a silicon carbide (SiC) substrate, a zinc oxide (ZnO) substrate, a silicon substrate, a gallium phosphide (GaP) substrate, and a gallium arsenide (GaAs) substrate.

Claim 5. (original) The UV photodetector of claim 1, wherein the high-resistivity GaN-based interlayer is constructed by doping at least one dopant selected from a group consisting of iron (Fe), magnesium (Mg), zinc (Zn), copper (Cu), arsenide (As), phosphorus (P), carbon (C) and beryllium (Be) or by a GaN-based semiconductor layer formed by a low temperature process (a temperature of growth less than 800°C).

Claim 6. (cancelled)

Claim 7. (currently amended) The UV photodetector of claim 61, wherein a material of the nucleation layer comprises $\text{Al}_a\text{In}_b\text{Ga}_{1-a-b}\text{N}$ semiconductor, wherein $a, b \geq 0$ and $0 \leq a + b \leq 1$.

Claim 8. (currently amended) The UV photodetector of claim 61, wherein a material of the ohmic contact layer comprises N-type $\text{Al}_c\text{In}_d\text{Ga}_{1-c-d}\text{N}$ semiconductor, wherein $c, d \geq 0$ and $0 \leq c + d \leq 1$.

Claim 9. (currently amended) The UV photodetector of claim 61, wherein a material of the active layer comprises undoped $\text{Al}_e\text{In}_f\text{Ga}_{1-e-f}\text{N}$ semiconductor, wherein $e, f \geq 0$ and $0 \leq e + f \leq 1$.

Claim 10. (original) The UV photodetector of claim 1, wherein a material of the first

Customer No.: 31561
 Application No.: 10/707,084
 Docket No.: 10722-US-PA

electrode and the second electrode comprises Ni/Au, Cr/Au, Cr/Pt/Au, Ti/Al, Ti/Al/Ti/Au, Ti/Al/Pt/Au, Ti/Al/Ni/Au, Ti/Al/Ti/Au, Ti/Al/Pd/Au, Ti/Al/Cr/Au, Ti/Al/Co/Au, Cr/Al/Cr/Au, Cr/Al/Pt/Au, Cr/Al/Pd/Au, Cr/Al/Ti/Au, Cr/Al/Co/Au, Cr/Al/Ni/Au, Pd/Al/Ti/Au, Pd/Al/Pt/Au, Pd/Al/Ni/Au, Pd/Al/Pd/Au, Pd/Al/Cr/Au, Pd/Al/Co/Au, Nd/Al/Pt/Au, Nd/Al/Ti/Au, Nd/Al/Ni/Au, Nd/Al/Cr/Au, Nd/Al/Co/Au, Hf/Al/Ti/Au, Hf/Al/Pt/Au, Hf/Al/Ni/Au, Hf/Al/Pd/Au, Hf/Al/Cr/Au, Hf/Al/Co/Au, Zr/Al/Ti/Au, Zr/Al/Pt/Au, Zr/Al/Ni/Au, Zr/Al/Pd/Au, Zr/Al/Cr/Au, Zr/Al/Co/Au, TiN_x/Ti/Au, TiN_x/Pt/Au, TiN_x/Ni/Au, TiN_x/Pd/Au, TiN_x/Cr/Au, TiN_x/Co/Au, TiWN_x/Ti/Au, TiWN_x/Pt/Au, TiWN_x/Ni/Au, TiWN_x/Pd/Au, TiWN_x/Cr/Au, TiWN_x/Co/Au, NiAl/Pt/Au, NiAl/Cr/Au, NiAl/Ni/Au, NiAl/Ti/Au, Ti/NiAl/Pt/Au, Ti/NiAl/Ti/Au, Ti/NiAl/Ni/Au, Ti/NiAl/Cr/Au, N-type conductive indium tin oxide (ITO), cadmium tin oxide (CTO), aluminum zinc oxide (ZnO:Al), indium zinc oxide (ZnO:In), zinc gallate (ZnGa₂O₄), SnO₂:Sb, Ga₂O₃:Sn, AgInO₂:Sn, In₂O₃:Zn, P-type conductive CuAlO₂, LaCuOS, NiO, CuGaO₂ or SrCu₂O₂.

Claim 11. (currently amended) An UV photodetector, comprising:

- a substrate;
- a GaN-based semiconductor layer, disposed on the substrate;
- a high-resistivity GaN-based interlayer, disposed on the GaN-based semiconductor layer,
- and a material of the GaN-based interlayer comprises Al_xIn_yGa_{1-x-y}N, wherein $x \geq 0$, $y \geq 0$, $1 \geq x + y$; and
- a first electrode; and
- a second electrode, wherein the first electrode comprises a plurality of first

Customer No.: 31561
Application No.: 10/707,084
Docket No.: 10722-US-PA

finger-shaped protrusions, the second electrode comprises a plurality of second finger-shaped protrusions, and the first finger-shaped protrusions and the second finger-shaped protrusions are mutually interlaced a patterned-electrode layer disposed on the GaN-based interlayer.

Claim 12. (cancelled)

Claim 13. (cancelled)

Claim 14. (currently amended) The UV photodetector of claim ~~12~~11, further comprises a first bonding pad, wherein the first bonding pad is disposed on the first electrode.

Claim 15. (currently amended) The UV photodetector of claim ~~12~~11, further comprises a second bonding pad, wherein the second bonding pad is disposed on the second electrode.

Claim 16. (original) The UV photodetector of claim 11, wherein the substrate is comprised an aluminum oxide (sapphire) substrate, a silicon carbide (SiC) substrate, a zinc oxide (ZnO) substrate, a silicon substrate, a gallium phosphide (GaP) substrate, and a gallium arsenide (GaAs) substrate.

Claim 17. (original) The UV photodetector of claim 11, wherein the high-resistivity GaN-based interlayer is constructed by doping at least one dopant selected from a group consisting of iron (Fe), magnesium (Mg), zinc (Zn), copper (Cu), arsenide (As), phosphorus (P), carbon (C) and beryllium (Be) or by a GaN-based semiconductor layer formed by a low temperature process (a temperature of growth less than 800°C).

Claim 18. (original) The UV photodetector of claim 11, wherein the GaN-based semiconductor layer comprising:

a nucleation layer, disposed on the substrate; and

Customer No.: 31561
 Application No.: 10/707,084
 Docket No.: 10722-US-PA

an active layer, disposed on the nucleation layer.

Claim 19. (original) The UV photodetector of claim 18, wherein a material of the nucleation layer comprises $\text{Al}_a\text{In}_b\text{Ga}_{1-a-b}\text{N}$ semiconductor, wherein $a, b \geq 0$ and $0 \leq a + b \leq 1$.

Claim 20. (original) The UV photodetector of claim 18, wherein a material of the active layer comprises undoped $\text{Al}_e\text{In}_f\text{Ga}_{1-e-f}\text{N}$ semiconductor, wherein $e, f \geq 0$ and $0 \leq e + f \leq 1$.

Claim 21. (original) The UV photodetector of claim 11, wherein a material of the patterned electrode layer comprises Ni/Au, Cr/Au, Cr/Pt/Au, Ti/Al, Ti/Al/Ti/Au, Ti/Al/Pt/Au, Ti/Al/Ni/Au, Ti/Al/Ti/Au, Ti/Al/Pd/Au, Ti/Al/Cr/Au, Ti/Al/Co/Au, Cr/Al/Cr/Au, Cr/Al/Pt/Au, Cr/Al/Pd/Au, Cr/Al/Ti/Au, Cr/Al/Co/Au, Cr/Al/Ni/Au, Pd/Al/Ti/Au, Pd/Al/Pt/Au, Pd/Al/Ni/Au, Pd/Al/Pd/Au, Pd/Al/Cr/Au, Pd/Al/Co/Au, Nd/Al/Pt/Au, Nd/Al/Ti/Au, Nd/Al/Ni/Au, Nd/Al/Cr/Au, Nd/Al/Co/Au, Hf/Al/Ti/Au, Hf/Al/Pt/Au, Hf/Al/Ni/Au, Hf/Al/Pd/Au, Hf/Al/Cr/Au, Hf/Al/Co/Au, Zr/Al/Ti/Au, Zr/Al/Pt/Au, Zr/Al/Ni/Au, Zr/Al/Pd/Au, Zr/Al/Cr/Au, Zr/Al/Co/Au, $\text{TiN}_x/\text{Ti/Au}$, $\text{TiN}_x/\text{Pt/Au}$, $\text{TiN}_x/\text{Ni/Au}$, $\text{TiN}_x/\text{Pd/Au}$, $\text{TiN}_x/\text{Cr/Au}$, $\text{TiN}_x/\text{Co/Au}$, $\text{TiWN}_x/\text{Ti/Au}$, $\text{TiWN}_x/\text{Pt/Au}$, $\text{TiWN}_x/\text{Ni/Au}$, $\text{TiWN}_x/\text{Pd/Au}$, $\text{TiWN}_x/\text{Cr/Au}$, $\text{TiWN}_x/\text{Co/Au}$, NiAl/Pt/Au, NiAl/Cr/Au, NiAl/Ni/Au, NiAl/Ti/Au, Ti/NiAl/Pt/Au, Ti/NiAl/Ti/Au, Ti/NiAl/Ni/Au, Ti/NiAl/Cr/Au, N-type conductive indium tin oxide (ITO), cadmium tin oxide (CTO), aluminum zinc oxide (ZnO:Al), indium zinc oxide (ZnO:In), zinc gallate (ZnGa_2O_4), $\text{SnO}_2:\text{Sb}$, $\text{Ga}_2\text{O}_3:\text{Sn}$, $\text{AgInO}_2:\text{Sn}$, $\text{In}_2\text{O}_3:\text{Zn}$, P-type conductive CuAlO_2 , LaCuOS , NiO, CuGaO_2 or SrCu_2O_2 .

BEST AVAILABLE COPY